FLOS

SKYGARDEN I ECO

Mounting Type of ceiling pendant Lamps description Environment	Pendant Suspension steel cable I x 32W Gx24q-3 Indoor
Finish	Glossy white, Glossy black, Matt gold, Matt rusty brown
Technical description	Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy, liquid- painted white. Molded upper bushing in die-cast, polished aluminum alloy, protected with transparent paint on the entire visible part. Upper cable gland and blocking ring nut in black injection-molded PC (polycarbonate). Shaped, galvanized adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp holder and fixing support in black injection-molded PPS (polyphenylene sulfide). Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Skygarden I frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment Gray, injection- molded PA6 (Nylon) rose.



Skygarden I ECO

designed by Marcel Wanders

Suspension luminaire providing diffused lighting.



DIMENSIONS


ELECTRICAL

Control gear availability	Included
Control gear mounting	Integral
Control gear type	Electronic
Emergency	Without
Voltage (V)	230

PHYSICAL

Supply	Terminal block
Cord length (mm)	3500
Construction material	Glass, Plaster, Stainless steel
Weight (kg)	13.6









Skygarden I ECO . Lamps



FSMH 32W GX24q-3

Lamp wattage: 32 W Lamp category: Compact fluorescent

Socket: GX24q-3

Lamp type: FSMH




Skygarden I ECO

designed by Marcel Wanders

Suspension luminaire providing diffused lighting.



DIMENSIONS







CE

IP 20



